

Bayslick Release Agent 20

Superior Form Release Agent for Precast Concrete

Bayslick Release Agent 20 is a premium concrete form release compound that produces superior results. It reactively prevents the bonding of forms and concrete mixtures and assures clean, positive stripping. Designed especially for aluminum forms used in the Precast industry, **Bayslick Release Agent 20** provides high-quality results in all form types regardless of their materials. Product surfaces are stain-free, bug holes and voids are eliminated, and finishes are suited for architectural Precast requirements.

Bayslick Release Agent 20 ensures lasting protection for all forms including those made from steel or wood. It helps waterproof wood and has anti-corrosive properties to keep steel forms free from deposit build-up, protected against the elements and rust, and ready for service. Easily applied via sprayer, brush, swab or by dipping, **Bayslick Release Agent 20** only requires a thin film to work effectively. It is used as a rust preventative for steel forms in storage and as a general preservative and cleaning agent for tools and equipment used in concrete mixing. Application rate is 1,600 – 3,800 square feet per gallon.

Bayslick Release Agent 20 provides the following benefits:

- Excellent release performance on aluminum molds
- Superior finishes that are smooth, white, and free from bug holes
- Extended form life for plywood and patented wall forms
- Rust and deposit build-up prevention for steel pan and column forms
- Easily applied in a thin film via sprayer, brush, swap or by dipping
- Reactive release agent, 1 gallon used per 1,600 – 3,800 square foot



Bay Oil Company
38 Plainfield Street
Chicopee, Ma. 01013
Ph: (413) 737-7808

TYPICAL PROPERTIES

API Gravity	38
Viscosity, cSt @ 40 °C	4.5
Flash Point, TCC, °F	125
Pour Point, °F	-15
Color	Amber
VOC (g/l)	434