

Bayslick Release Agent 72

Form Release Agent for Foundational Concrete

Bayslick Release Agent 72 is a specially formulated release compound that acts chemically to prevent bonding between forms and concrete mixtures. Designed to leave a smooth finish and help keep forms clean of concrete deposits, **Bayslick Release Agent 72** eliminates the need for chipping and wire brushing to prepare forms for additional use. It leaves surfaces of finished concrete pieces are white, smooth, and free from bug holes, with less distortion and breakage.

Bayslick Release Agent 72 provides lasting protection for wooden and steel forms. Its' pleasant cherry odor, waterproofing effect, and anti-corrosive properties keep forms free from deposit build-up, protected against the elements and rust, and ready for continuous service. Easily applied via sprayer, brush, swab or by dipping, **Bayslick Release Agent 72** only requires a thin film to work effectively. It is used as a rust preventative for steel forms in storage and as a general preservative and cleaning agent for tools and equipment used in concrete mixing. Application rate is 1,000 – 3,000 square feet per gallon.

Bayslick Release Agent 72 provides the following benefits:

- Finished surfaces are smooth, white, and free from bug holes
- Extends the form life of plywood and patented wall forms,
- Prevents rust and deposit build-up for steel pan and column forms
- Thin film is easily applied via sprayer, brush, swap or by dipping
- Reactive release agent, 1 gallon used per 1,000 – 3,000 square foot
- Pleasant odor for better handling



Bay Oil Company
38 Plainfield Street
Chicopee, Ma. 01013
Ph: (413) 737-7728

TYPICAL PROPERTIES

API Gravity	30
Viscosity, cSt @ 40 °C	11
Flash Point, TCC, °F	225
Pour Point, °F	-15
Color	Straw
VOC (g/l)	190